



INDOOR BREAKOUT CABLE

FEATURES

- 2 to 24 fibers. Higher fiber counts are available upon request.
- Rugged cable design.
- Design for direct termination with standard connectors.
- Each core is strain-relieved.
- Outer Jacket also available in Frame Retardant (FR) and Low Smoke Zero Halogen. (LSZH)

APPLICATIONS

- Multicore pre-terminated patchcord cable assemblies.
- Horizontal and Collapsed Backbone cable.
- Installation in indoor area.

ITEM		DESCRIPTION					
Fiber Count		4	6	8	10	12	24
Central Strength Member		2.25mm		4.7mm		6.8mm	
Tight Buffer Diameter		900 µm					
Inner Cable Diameter		2.0mm					
Cable	Diameter	9.1mm	9.5mm	11.0mm	12.8mm	14.1mm	21.5mm
	Weight	63kg/km	88kg/km	131kg/km	154kg/km	187kg/km	325kg/km
Maximum Pulling Tension		600 N					
Crush Resistance		20 N/mm					
Storage Temperature		-40° C ~ +85° C					
Operating Temperature		-20° C ~ +85° C					
Bending Radius	Static	91mm	95mm	110mm	128mm	141mm	215mm
	Dynamic	182mm	190mm	221mm	256mm	282mm	430mm