



FIBER OPTIC 19” RACK MOUNTED DISTRIBUTION PANEL- HIGH DENSITY

DESCRIPTION

The case is made of cold rolled steel sheet, electrostatic spraying, provide capacity up to 96/192 port fiber. Available for SC, FC, LC & E2000.

FEATURES

- 3U, 4U & 6U design - Space saving 19” Rack Installation.
- Cable guards to ensure good routing for incoming fiber.
- Up to 192 Adaptor Port (Depends on adaptor type).
- Incorporated with splice Trays.
- Interchangeable tray to allow maximum flexibility of adaptor choice.

APPLICATIONS

- Installed inside equipment rack.
- Backbone fiber termination & distribution.
- Main Distribution Frame (MDF).
- Local Area Network (LAN).
- Wide Area Network (WAN).
- Close Circuit Television (CCTV).
- Data Centre.
- Optical Distribution Frame (ODF) for FTTH System.



FIBER OPTIC 19" RACK MOUNTED DISTRIBUTION PANEL- HIGH DENSITY



SPEC	DESCRIPTION
Material	Mild Steel
Color	Beige Powder Epoxy
Weight	4.30 kg (3U) 5.50 kg (4U) 7.80 kg (6U)
Adaptor Capacity	96/192
Tray Capacity	4 (3U) 6 (4U) 8 (6U)
Operating Temperature	-25°C ~ +40°C
Storage Temperature	-25°C ~ +55°C
Dimension (H X W X D)	132 X 483 X 300 mm (3U) 176 X 483 X 300 mm (4U) 265 X 483 X 300 mm (6U)