



FIBER OPTIC 19” RACK MOUNTED DISTRIBUTION PANEL

DESCRIPTION

The case is made of cold rolled steel sheet, electrostatic spraying, provide capacity up to 24/48 port fiber. Available for ST, SC, FC, LC & E2000.

FEATURES

- 1U design - Space saving 19” Rack Installation
- Cable Grand to provide maximum cable retention
- Cable guards to ensure good routing for incoming fiber
- Up to 48 Adaptor Port (Depends on adaptor type)
- Splice Trays are allowed to install
- Interchangeable front panel to allow maximum flexibility of adaptor choice

APPLICATIONS

- Installed inside equipment rack
- Backbone fiber termination & distribution
- Main Distribution Frame (MDF)
- Local Area Network (LAN)
- Wide Area Network (WAN)
- Close Circuit Television (CCTV)
- Data Centre



FIBER OPTIC 19” RACK MOUNTED DISTRIBUTION PANEL



SPEC	DESCRIPTION
Material	Mild Steel
Color	Black Powder Epoxy
Weight	3.10 kg
Adaptor Capacity	48
Splice Tray Capacity	3
Operating Temperature	-25°C ~ +40°C
Storage Temperature	-25°C ~ +55°C
Dimension (H X W X D)	44 X 480 X 206 mm