



FIBER OPTIC WALL MOUNTED DISTRIBUTION BOX

DESCRIPTION

The case is made of cold rolled steel sheet, electrostatic spraying, provide capacity up to 48/96 port fiber. Available for ST, SC, FC, LC & E2000.

FEATURES

- 2 Lockable Doors design – Better Security & Flexibility.
- Cable Grand to provide maximum cable retention.
- Cable guards to ensure good routing for incoming fiber.
- Up to 96 Adaptor Port (Depends on adaptor type).
- Splice Trays are allowed to install.
- Interchangeable panel to allow maximum flexibility of adaptor choice.

APPLICATIONS

- Installed on wall.
- Backbone fiber termination & distribution.
- Main Distribution Frame (MDF).
- Local Area Network (LAN).
- Wide Area Network (WAN).
- Close Circuit Television (CCTV).
- Data Centre.
- Backbone fiber termination & distribution.



FIBER OPTIC WALL MOUNTED DISTRIBUTION BOX



SPEC	DESCRIPTION
Material	Mild Steel
Color	Beige Color Powder Epoxy
Weight	5.00 kg (up to 24/48 port) 6.50 kg (up to 48/96 port)
Adaptor Capacity	24/48 48/96
Splice Tray Capacity	4 or 8
Operating Temperature	-25°C ~ +40°C
Storage Temperature	-25°C ~ +55°C
Dimension (H X W X D)	380 X 400 X 80 mm (up to 24/48 port) 380 X 400 X 140 mm (up to 48/96 port)